

SN 09/920,230

- 2 -

**Amendments to the Claims**

The listing of claims below is intended to replace all prior listings of the claims in the present application.

1. (currently amended) A feeder chute comprising:  
a bottom member having a first end which defines a receiving zone and  
a second end which defines a discharge zone;

a plurality of channels formed in the bottom member within the  
discharge zone and extending in the direction between the first and second ends, wherein one  
of the plurality of channels has a terminus defining a first discharge plane and a second  
channel adjacent to the one channel has a terminus defining a second discharge plane, the  
second discharge plane being spaced apart from the first discharge plane;

wherein the terminus of each channel is free from any encumbrance.

2. (original) The feeder chute according to claim 2, wherein the bottom  
member includes a portion between the first and second ends which defines an alignment  
zone, the feeder chute further comprising:

means for aligning an object traveling through the alignment zone, the  
means for aligning causing the object to be aligned with its length axis extending  
substantially in a direction between the first and second ends of the bottom member.

3. (original) The feeder chute according to claim 2, wherein the means  
for aligning comprise:

a plurality of spaced projections extending upwardly from the bottom  
member within the alignment zone.

4. (original) The feeder chute according to claim 3, wherein the plurality  
of projections comprise:

at least one linear array of spaced projections extending upwardly from  
the bottom member to define two or more passages each of which is co-extensive with a  
single channel of the plurality of channels.

SN 09/920,230

- 3 -

5. (original) The feeder chute according to claim 4, wherein the plurality of projections further comprise:

at least one projection extending upwardly from the bottom member, the at least one projection being spaced apart from the linear array of projections and within one of the two or more passages defined by the linear array of projections.

6. (original) The feeder chute according to claim 4, wherein the projections are individually or collectively removable.

7. (original) The feeder chute according to claim 3, wherein each of the plurality of spaced projections is substantially cylindrical.

8. (withdrawn) The feeder chute according to claim 1, wherein each of the plurality of channels further comprises a slot extending at least partially the length of each channel.

9. (withdrawn) The feeder chute according to claim 8, wherein the slot of each channel extends to a position which is about 10 centimeters from the discharge plane thereof.

10. (original) The feeder chute according to claim 1, wherein the distance between the discharge plane of adjacent channels is substantially the same as the distance between troughs of adjacent channels.

11. (withdrawn) A feeder chute and a conveyor system in combination, the feeder chute comprising:

a bottom member having a first end which defines a receiving zone and a second end which defines a discharge zone, and

a plurality of channels formed in said bottom member within the discharge zone and extending in the direction between the first and second ends; and the conveyor system comprising:

a plurality of conveyors, each conveyor being aligned beneath one of the plurality of channels of the feeder chute, and each conveyor including a drive wheel operatively coupled to a drive shaft, one or more driven wheels, and a conveyor belt suspended on the drive wheel and the one or more driven wheels, and

SN 09/920,230

- 4 -

drive means, coupled to the drive shaft of each conveyor, for driving revolution of each of the plurality of conveyors;  
wherein one of said conveyors forms a terminus defining a first discharge plane and a second conveyor adjacent to said one conveyor forms a terminus defining a second discharge plane, the second discharge plane being spaced from said first discharge plane.

12. (withdrawn) The feeder chute and conveyor system according to claim 11, wherein the drive means comprises and a motor operatively coupled to the drive shaft.

13. (withdrawn) The feeder chute and conveyor system according to claim 11, wherein drive shaft for each conveyor is a common drive shaft and the drive means is coupled to the common drive shaft.

14. (withdrawn) The feeder chute and conveyor system according to claim 11, wherein the conveyor belts for the plurality of conveyors all rotate at a constant linear velocity.

15. (withdrawn) The feeder chute and conveyor system according to claim 11, wherein the distance between the discharge plane of adjacent conveyors is substantially the same as the distance between troughs of adjacent channels.

16. (withdrawn) A system for capturing multiple images of an object, the system comprising:  
means, in communication with a source of objects, for delivering an object into an image capture zone whereby the object passes through a predetermined point in space within the image capture zone;  
a first image capture device located a first predetermined distance from the predetermined point in space; and  
a second image capture device located a first predetermined distance from the predetermined point in space, the second image capture device being substantially 90 degrees offset from the first image capture device.

SN 09/920,230

- 5 -

17. (withdrawn) The system according to claim 16, wherein said means for delivering comprises a feeder chute comprising:

a bottom member having a first end which defines a receiving zone and a second end which defines a discharge zone;

a plurality of channels formed in the bottom member within the discharge zone and extending in the direction between the first and second ends, wherein one of the plurality of channels has a terminus defining a first discharge plane and a second channel adjacent to the one channel has a terminus defining a second discharge plane, the second discharge plane being spaced apart from the first discharge plane.

18. (withdrawn) The system according to claim 16, wherein said means for delivering comprises a feeder chute in combination with a conveyor system, the feeder chute comprising:

a bottom member having a first end which defines a receiving zone and a second end which defines a discharge zone, and

a plurality of channels formed in said bottom member within the discharge zone and extending in the direction between the first and second ends; and the conveyor system comprising:

a plurality of conveyors, each conveyor being aligned beneath one of the plurality of channels of the feeder chute, and each conveyor including a drive wheel operatively coupled to a drive shaft, one or more driven wheels, and a conveyor belt suspended on the drive wheel and the one or more driven wheels, and

drive means, coupled to the drive shaft of each conveyor, for driving revolution of each of the plurality of conveyors;

wherein one of said conveyors forms a terminus defining a first discharge plane and a second conveyor adjacent to said one conveyor forms a terminus defining a second discharge plane, the second discharge plane being spaced from said first discharge plane.

19. (withdrawn) The system according to claim 16 further comprising: one or more light sources which illuminate the image capture zone.

20. (withdrawn) The system according to claim 19, wherein the one or more light sources are selected from the group consisting of a strobe light, a strobed LED, a continuous fluorescence high frequency light, and combinations thereof.

SN 09/920,230

- 6 -

21. (withdrawn) The system according to claim 16 further comprising:  
a processor in communication with said first and second image capture devices.

22. (withdrawn) A system for capturing multiple images of an object, the system comprising:

means, in communication with a source of objects, for delivering an object into an image capture zone whereby the object passes through a predetermined point in space within the image capture zone;

an image capture device located a predetermined distance from the predetermined point in space; and

a mirror positioned within the image capture zone to reflect a reflected image of the object which is substantially 90 degrees offset from a direct image presented to the image capture device;

wherein the image capture device captures both the direct image and the reflected image simultaneously;

23. (withdrawn) The system according to claim 22, wherein said means for delivering comprises a feeder chute comprising:

a bottom member having a first end which defines a receiving zone and a second end which defines a discharge zone;

a plurality of channels formed in the bottom member within the discharge zone and extending in the direction between the first and second ends, wherein one of the plurality of channels has a terminus defining a first discharge plane and a second channel adjacent to the one channel has a terminus defining a second discharge plane, the second discharge plane being spaced apart from the first discharge plane.

SN 09/920,230

- 7 -

24. (withdrawn) The system according to claim 22, wherein said means for delivering comprises a feeder chute in combination with a conveyor system, the feeder chute comprising:

a bottom member having a first end which defines a receiving zone and a second end which defines a discharge zone, and

a plurality of channels formed in said bottom member within the discharge zone and extending in the direction between the first and second ends; and the conveyor system comprising:

a plurality of conveyors, each conveyor being aligned beneath one of the plurality of channels of the feeder chute, and each conveyor including a drive wheel operatively coupled to a drive shaft, one or more driven wheels, and a conveyor belt suspended on the drive wheel and the one or more driven wheels, and

drive means, coupled to the drive shaft of each conveyor, for driving revolution of each of the plurality of conveyors;

wherein one of said conveyors forms a terminus defining a first discharge plane and a second conveyor adjacent to said one conveyor forms a terminus defining a second discharge plane, the second discharge plane being spaced from said first discharge plane.

25. (withdrawn) The system according to claim 22 further comprising: one or more light sources which illuminate the image capture zone.

26. (withdrawn) The system according to claim 25, wherein the one or more light sources are selected from the group consisting of a strobe light, a strobed LED, a continuous fluorescence high frequency light, and combinations thereof.

27. (withdrawn) The system according to claim 22 further comprising: a processor in communication with said image capture device.

28-31 (canceled)